





- 1. DISTORTION adjusts the amount of distortion gain.
- 2. DEPTH adjusts the low frequency 'growl' of extended range instruments.
- 3. LEVEL adjusts the overall output level of the distortion effect.
- 4. LOW adjusts the low EQ frequency and its level.
- 5. MID adjusts the mid EQ frequency and its level.
- 6. HIGH adjusts the high EQ frequency and its level.
- 7. INPUT connect your instrument here.
- 8. FOOTSWITCH turns the effect on and off.
- 9. LED turns on when the effect is enabled.
- 10. OUTPUT connect to the next pedal's input or to the input of your amplifier.

USING BONESHAKER:

Most guitarists/bassists will favor placing the Boneshaker at the beginning of their chain of effects, so start with that placement.

A typical effects signal chain will consist of Distortion effects first then Modulation

effects (Chorus, Flanger, Phaser, Tremolo, etc...) next and then finally Time based effects (Delay and Reverb).

Placing the Boneshaker toward the front of your chain or effects will preserve vibe no matter the pedal combination that follows. You may wish to experiment with the effect placement since Boneshaker also stacks well with other distortions and fuzz!

SPECIFICATIONS:

Input 1/4	"TS Unbalanced - 470 k $\Omega$
-----------	---------------------------------

- Output 1/4'' TS Unbalanced 100  $\Omega$
- Current Draw 20 mA

Bypass True Bypass

Power 9VDC alkaline battery (not included) HARMAN PS200R power adapter (optional)

Warranty 1 Year



DOD 10653 River Front Parkway South Jordan, UT 84095 USA 801-566-8800